

TIMECUTTER® HD		with MyRIDE® SUSPENSION SYSTEM				
		75201	75202	75211	75212	75213
COMMERCIAL-GRADE CONSTRUCTION	ENGINE ¹	22.5 hp Toro® Commercial V-Twin	» 24.5 hp Toro Commercial V-Twin	22.5 hp Toro Commercial V-Twin	» 24.5 hp Toro Commercial V-Twin	24.5 hp Toro Commercial V-Twin
	MOWING DECK	48" (121.9 cm) Fabricated - Grade 50 High Strength 10 ga. Steel Shell	» 54" (137.2 cm) Fabricated - Grade 50 High Strength 10 ga. Steel Shell	48" (121.9 cm) Fabricated - Grade 50 High Strength 10 ga. Steel Shell	» 54" (137.2 cm) Fabricated - Grade 50 High Strength 10 ga. Steel Shell	» 60" (152.4 cm) Fabricated - Grade 50 High Strength 10 ga. Steel Shell
	FRONT AXLE	2.5" x 2.5" (6.4 x 6.4 cm) Fully Tubular	2.5" x 2.5" (6.4 x 6.4 cm) Fully Tubular	2.5" x 2.5" (6.4 x 6.4 cm) Fully Tubular	2.5" x 2.5" (6.4 x 6.4 cm) Fully Tubular	2.5" x 2.5" (6.4 x 6.4 cm) Fully Tubular
	FUEL CAPACITY	5 Gallons (18.9 L)	5 Gallons (18.9 L)	5 Gallons (18.9 L)	5 Gallons (18.9 L)	5 Gallons (18.9 L)
	FRAME	Heavy-Duty 10 Gauge	Heavy-Duty 10 Gauge	Heavy-Duty 10 Gauge	Heavy-Duty 10 Gauge	Heavy-Duty 10 Gauge
	DECK WASHOUT PORTS	2 Standard	2 Standard	2 Standard	2 Standard	2 Standard
	DECK SPINDLES	7.75" (19.7 cm) dia. housing 1" (2.5 cm) dia. shaft	7.75" (19.7 cm) dia. housing 1" (2.5 cm) dia. shaft	7.75" (19.7 cm) dia. housing 1" (2.5 cm) dia. shaft	7.75" (19.7 cm) dia. housing 1" (2.5 cm) dia. shaft	7.75" (19.7 cm) dia. housing 1" (2.5 cm) dia. shaft
	BLADE-TIP SPEED	18,880+ ft/min (5,755+ m/min)	18,644+ ft/min (5,683+ m/min)	18,880+ ft/min (5,755+ m/min)	18,644+ ft/min (5,683+ m/min)	18,908+ ft/min (5,763+ m/min)
	ANTI-SCALP ROLLERS	3 Standard	3 Standard	3 Standard	3 Standard	3 Standard
	DECK LIFT PEDAL	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position
	TRANSMISSIONS	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100
	GROUND SPEED ²	Up to 8.5 mph (13.7 km/h)	Up to 8.5 mph (13.7 km/h)	Up to 8.5 mph (13.7 km/h)	Up to 8.5 mph (13.7 km/h)	Up to 8.5 mph (13.7 km/h)
TIRES (REAR)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	
TIRES (FRONT)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	
BEST-IN-CLASS COMFORT	SEAT	18" (46 cm) Thickly Padded Premium	18" (46 cm) Thickly Padded Premium	18" (46 cm) Thickly Padded Premium	18" (46 cm) Thickly Padded Premium	18" (46 cm) Thickly Padded Premium
	SEAT SUSPENSION	Springs Under Seat	Springs Under Seat	» MyRide® Suspension System	MyRide Suspension System	MyRide Suspension System
	ARMRESTS	Standard	Standard	Standard	Standard	Standard
	STEERING LEVERS	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers
	ANTI-VIBRATION FLOOR MAT	Standard	Standard	Standard	Standard	Standard
UNMATCHED VERSATILITY	HITCH	Standard	Standard	Standard	Standard	Standard
	12V ACCESSORY PORT	Standard	Standard	Standard	Standard	Standard
	REAR ENGINE GUARD	Standard, Bucket Ready	Standard, Bucket Ready	Standard, Bucket Ready	Standard, Bucket Ready	Standard, Bucket Ready
	SMART SPEED® CONTROL SYSTEM	Standard	Standard	Standard	Standard	Standard
OTHER FEATURES	STORAGE DIMENSIONS (W x L x H)	82" x 52.4" x 44" (208.3 x 133.1 x 111.8 cm)	82" x 57.7" x 44" (208.3 x 146.6 x 111.8 cm)	82" x 52.4" x 44" (208.3 x 133.1 x 111.8 cm)	82" x 57.7" x 44" (208.3 x 146.6 x 111.8 cm)	82" x 63" x 44" (208.3 x 160 x 111.8 cm)
	ROPS (FOLDABLE FOR STORAGE)	Optional	Optional	Optional	Optional	Optional
	HOURLY METER	Standard	Standard	Standard	Standard	Standard
	LIMITED WARRANTY ³	3 year / 300 hour	3 year / 300 hour	3 year / 300 hour	3 year / 300 hour	3 year / 300 hour

» = Enhanced or Step-up feature



490-9957 ©2018 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. ¹The gross or net horsepower ratings of these engines were laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower. ²Maximum ground speed will vary with ground conditions, tire pressure, transmission settings and engine settings. ³See retailer for warranty details.